

MIXERS



| MIXEK2 | |
|---------------------------------------------|----|
| IPERBET | Gź |
| IPERBET FLUID | G |
| FLUID MATERIALS MIXERS | |
| FLUID MIX | G۷ |
| FLUID MIX SPECIAL | G، |
| MIXERS | |
| MX3: MIXER WITH 2 VARIABLE SPEEDS 1600 WATT | G! |
| BUCKETS AND MIXING PADDLES | |
| ACCESSORIES, BUCKETS AND MIXING PADDLES | G |







Compact mixers, mixing paddles, the innovative mixers with two variable speeds: a complete range of products for mixing adhesives and grout for ceramic tiles as well as concrete, quartz plaster, cement, mortars, screeds, epoxy resins. Furthermore, a range of products specifically designed for mixing and setting of fluid mixtures such as self-leveling, premixed, paint, etc.



































- \bullet For mixing tile adhesives, thinsets, mortar for plasters, quartz plasters, concrete and etc...
- Production capacity 300 Kg/h (50 lbs 100 lbs).
- Mixing at low rpms does not entrap air and provides a homogenous mix.
- Fixed paddle, rotating bucket. This system provides a higher level of operator safety and allows the operator to check the mix quality while mixing.
- \bullet Gear ratio of motor to bucket 25 \div 1.
- \bullet Supplied with: two buckets (45 lt/12 gal), standard mixing blade, hex key, user and maintenance manual.

| MODEL SPECIFICATION | JNS | | | | | | | |
|---------------------|---------------|---|----------------|--------------|----------------|-----------|---------|--------------|
| Part No. | | | N | M | | | | Lt |
| 110 | 8024648003331 | 1 | 230 V 50/60 Hz | Single-phase | 0,5 HP/0,37 kW | 1400/1680 | 55 / 66 | 45 lt 12 gal |
| 110 USA | 8024648014092 | 1 | 110 V 60 Hz | Single-phase | 0,5 HP/0,37 kW | 1680 | 66 | 45 lt 12 gal |
| 110 GR | 8024648005403 | 1 | 110 V 50 Hz | Single-phase | 0.5 HP/0.37 kW | 1400 | 55 | 45 lt 12 aal |

DIMENSIONS AND WEIGHT

| DIMENSIONS AND WEIGH | | | | |
|----------------------|-------------------------------------|--------------|-------------------------------------------|--------------|
| Model | | | | |
| IPERBET | 60x51xh 77 cm 23 5/8"x20"xh 30 1/4" | 34 Kg 75 lbs | 85x60xh 60 cm 33 1/2" x23 5/8" xh 23 5/8" | 39 Kg 86 lbs |

























TECHNICAL CHARACTERISTICS















- For mixing grout, tile adhesives and fluid material.
 Production capacity 300 Kg/h (50 lbs 100 lbs)
 Mixing at low rpms does not entrap air and provides a homogenous mix.
 Paddle is comprised of: fixed blade to force the mixture toward the center and a rotating tool for lump-free consistency.
- Gear ratio of motor to bucket $25 \div 1$.
- ullet Supplied with: two buckets 45 lt (12 gal), paddle for fluid mixing, hex key, user and maintenance manual.

| MODEL SPECIFICATION | > | | | | | | | |
|---------------------|---------------|---|----------------|--------------|----------------|-----------|---------|--------------|
| Part No. | | | N | M | | | | Lt . |
| 110 FLUID | 8024648011374 | 1 | 230 V 50/60 Hz | Single-phase | 0,5 HP/0,37 kW | 1400/1680 | 55 / 66 | 45 lt 12 gal |
| 110 FLUUS | 8024648014948 | 1 | 110 V 60 Hz | Single-phase | 0,5 HP/0,37 kW | 1680 | 66 | 45 lt 12 gal |
| 110 FILIGR | 8024648014955 | 1 | 110 V 50 Hz | Single-phase | 0.5 HP/0.37 kW | 1400 | 55 | 45 lt 12 nal |

DIMENSIONS AND WEIGHT

| DIRECTIONS AND TELOTI | | | | | | | | | | |
|-----------------------|-------------------------------------|----------------|-----------------------------------------|----------------|--|--|--|--|--|--|
| Model | | | | | | | | | | |
| IPERBET FLUID | 60x51xh 77 cm 23 5/8"x20"xh 30 1/4" | 35 Kg 77.2 lbs | 85x60xh 60 cm 33 1/2"x23 5/8"xh 23 5/8" | 40 Kg 88.2 lbs | | | | | | |









- For mixing fluid materials such as self-leveling, premixed, cement-based grout, paint and others.
- Perfect mixing, time for mixing cut off 50%, it eliminates fatigue for transporting the materials once mixed.
- Sturdy steel frame, rubber wheels, dust-free cap.
- Available in two versions:

Art. 238 UN: 4 swivel wheels and inclinable bucket which allows to pour the mixture uniformly. Art. 238 EUN:2 fixed wheels and two levers for pouring the mixture.

- Buckets (Art. 289LT75) capacity:
- 75 liters (20 gal) of mixed material; 75/100 Kg (34/45 lbs) of dry (still to be mixed) material.
- Universal attachment for drills/mixers from Ø 40 mm to Ø 60 mm (1 9/16" 2 3/8").
- 3 spirals mixing-paddle (art.178389H); Ø 140 mm (5 1/2''); stem length: 680 mm (26 25/2''); screw attachment 14M.
- Equipped with: 1 bucket 75 liters (20 gal); 1 mixing-paddle, mixer not included.
- A conveyor for Fluid mix special bucket is available (Art. 238 CV01A).

MODEL SPECIFICATIONS

| Part No. | | | Description | • | u | Screw attachment |
|----------|---------------|---|------------------------------------------------|-------|--------|------------------|
| 238 UN | 8024648061096 | 1 | Fluid mix special - with paddle; without mixer | 75 lt | 20 gal | 14 M |
| 238 EUN | 8024648061089 | 1 | Fluid mix - with paddle; without mixer | 75 lt | 20 gal | 14 M |

DIMENSIONS AND WEIGHT

| Model | lodel Description | | | | ţ | | کے | |
|-------------------|----------------------------------------|--------------|----------------------------|----------------|-------------------|---------------------------|-------|----------|
| FLUID MIX SPECIAL | With mixing-paddle, mixer not included | 61x66xh 95cm | 24"x26"xh 37 1/2" | 28 Kg 61.7 lbs | 85x60xh 70 cm | 33 1/2"x23 5/8"xh 27 1/2" | 29 Kg | 63.9 lbs |
| FLUID MIX | With mixing-paddle, mixer not included | 54x60xh 77cm | 21 1/4"x 23 1/2"xh 30 3/8" | 17 Kg 37.5 lbs | ODKOUKII / U (III | JJ 1/2 XZJ 3/8 XII Z/ 1/2 | 18 Kg | 39.7 lbs |

REPLACEMENT PARTS/ACCESSORIES

| Part No. | | | Description | 1 | | \mathcal{C} | |
|-----------|---------------|---|-----------------------------------------------------------|----------------|-----------------------|---------------|---------|
| 238 CV01A | 8024648024299 | 1 | Conveyor for Fluid mix special bucket | 40x40x h 15 cm | 15 3/4"x15 3/4"x h 6" | 2,6 Kg | 5.7 lbs |
| 289LT75 | 8024648002495 | 1 | Buckets: capacity 75 liters (20 gal) | - | _ | - | - |
| 178389H | 8024648001603 | 1 | 3 spirals mixing-paddle; Ø140 mm (5 1/2"); attachment 14M | - | _ | - | _ |



















































- resins and so on... • Two variable speeds: first speed 180-460 rpm; second speed 300-750 rpm.
- Dual rotation speeds with electronic speed control.
 Double spiral mixing paddle included (Ø 140 mm 5 1/2") that can be dismantled.
- Ergonomic design (included handles provided with rubber inserts for optimal grip).
- Button for permanent run.

- Externally accessible brushes for greater service ability and longer motor life.
- Mixing paddle with screw clutch M14.
- 2 m (6.5') cable.

MODEL SPECIFICATIONS

| MODEL OF ECIFICATIONS | | | | | | | | | |
|-----------------------|---------------|---|----------|-------|-----------------|-----------------|--------|----|-----|
| Part No. | | | N | | Bos | Ø | , 1 | 15 | A S |
| 301W1600V2VSC | 8050532024267 | 1 | 230 V 50 | 1600W | 180/460-300/750 | 140 mm - 5 1/2" | • | • | • |

DIMENSIONS AND WEIGHT

| DIMENSIONS AND WEIGH | • | | | | | | | |
|----------------------|--------------------------------------------|--|--|----------|----------------|--------------------------|--------|----------|
| Model | † | | | | ţ | 2 | | |
| MX3 - 1600W | 46x 25x h 88 cm 18 1/6"x12 2/3"x h 34 2/3" | | | 11.5 lbs | 45x32x h 25 cm | 17 2/3"x 12 2/3" x h 10" | 6,2 Kg | 13.7 lbs |



















ACCESSORIESES FOR IPERBET, IPERBET FLUID AND MIXERS

| Part No. | | | Description | | <u> </u> | | | کے | |
|----------|---------------|----|-----------------------------------------------------------|--------|----------|----------------|------------------|--------|----------|
| 243 | 8024648070968 | 3 | Height-adjustable rake for self-leveling (without handle) | 1,6 Kg | 3.5 lbs | 71x23xh 12 cm | 28"x9"x h 4 1/2" | 5,2 Kg | 11.5 lbs |
| 243SL01A | 8050532012776 | 3 | Slides for rake 243 + screws (pair) | 135 gr | 4.8 | _ | - | - | - |
| 197CF | 8024648000316 | 12 | Anodized aluminum pole with hole - length 133 cm | 420 gr | 14.8 oz | 140x25xh 10 cm | 55"x10"x4" | 5,5 Kg | 12.1 lbs |
| 197CM180 | 8024648000644 | 12 | Anodized aluminum pole with hole - length 180 cm | 540 gr | 19 oz | 180x25xh 25 cm | 71"x10"x10" | 7 Kg | 15.4 lbs |

TOOLS

| Part No. | | | Description | IPERBET | IPERBET FLUID | ERBET FLUID | | | | | |
|------------|---------------|---|---------------------------------|----------|---------------|-------------|---------|---------------|----------------------|--------|---------|
| 239KITC01A | 8024648007094 | 1 | Tool kit for mixing fluidfluidi | • | standard | 2,9 Kg | 6.4 lbs | 58x30xh 25 cm | 23"x12"xh 10" | 3,4 Kg | 7.5 lb |
| 239UF02D | 8024648011442 | 1 | Double bladed tool | standard | • | 2 Kg | 4.4 lbs | 35x40xh 10 cm | 13 3/4"x15 3/4"xh 4" | 2,3 Kg | 5 lbs |
| 239VG02A | 8050532003774 | 1 | Mass (clump) breaker | • | _ | 370 gr | 13 oz | 35x5xh 5 cm | 13 3/4"x2"xh 2" | 470 gr | 16.6 oz |

BUCKETS

| Part No. | | | Description | Lt | IPERBET | IPERBET FLUID | <u></u> | | | | Ω |
|----------|---------------|---|---------------------|--------------|----------|---------------|--------------|---|---|---|---|
| 289IPER | 8024648000989 | 1 | Bucket with handles | 45 lt 12 gal | standard | standard | 2,3 Kg 5 lbs | _ | _ | _ | _ |

MIXING PADDLES

- For mixing paints, thin set, grout, ready render, etc...
 Type of clutches: with profiled arm for quick-release screw arm 14M for screw-fit, hexagonal arm for blocking with chuck.
- Type of shape: reinforced double spiral, 4 shaped blades.Made of galvanized steel.

| Part No. | | | Description | Ala. | # B | M& | ‡ [| | ĺ | S. |
|----------|---------------|----|------------------------------------------------|------|-----|----|------------------|------------------------|--------|----------|
| 178 389E | 8024648009814 | 1 | 4 bladed mixing paddle Ø 140 mm (5 3/4") | _ | • | - | | | - | - |
| 178 389L | 8024648079541 | 1 | Double spiral mixing paddle Ø 160 mm (6 9/32") | _ | • | _ | | | - | - |
| 178 389F | 8024648017888 | 1 | Double spiral mixing paddle Ø 140 mm (5 3/4") | _ | • | _ | _ | _ | - | - |
| 178 389G | 8024648017895 | 1 | Double spiral mixing paddle Ø 120 mm (4 3/4") | _ | • | _ | | | _ | - |
| 178 S | 8024648000392 | 10 | Double spiral mixing paddle Ø 90 mm (3 1/2") | _ | - | • | 60x34xh 20 cm | 23 5/8"x13 3/8"xh 8" | 5,7 Kg | 12.6 lbs |
| 178 | 8024648000385 | 16 | 4 bladed mixing paddle Ø 120 mm (4 3/4") | _ | _ | • | 00234211 20 (111 | 23 3/0 x 13 3/0 x 11 0 | 7,7 Kg | 17 lbs |
| 178D60 | 8024648056887 | 12 | Double spiral mixing paddle Ø 60 mm (2 3/8") | - | - | • | 44x15xh 14 cm | 17 1/3"x6"xh 5 1/2" | 2,8 Kg | 6.2 lbs |
| 178D80 | 8024648058195 | 12 | Double spiral mixing paddle Ø 80 mm (3 1/8") | _ | _ | • | 44x19xh 18 cm | 17 1/3″x7 1/2″xh 7″ | 3,1 Kg | 6.8 lbs |





