

ELECTROSPONGES



ELECTROSPONGES


BERTA ADV	L2
ROSINA	L3

ACCESSORIES AND TOOLS FOR ELETTROSPONGES

SPONGE ROLLERS AND ANTIFOAM LIQUID	L4
--	----




For cleaning the joints after grouting on medium and large-sized areas our range of electrosponges is the perfect solution. "Berta ADV" and "Rosina" leave the floor clean (whether it is porcelain, single or double-fired ceramic tiles, porphyry, terracotta, marble, etc.) and do not pull the grout out from joints. They give an output up to 100 sq. meter per hour and they allow to work in upright position, so, with the maximum comfort. That is to say that our electrosponges give perfect results, cut time, and cut to zero physical effort. Both with cement-based and epoxy-based grout. In addition to that, the pump-free exclusive system for transporting the water from the tank to the sponge roller, ensures matchless reliability and effectiveness.






AVAILABLE SPONGE



TECHNICAL CHARACTERISTICS



ACCESSORIES



PACKAGE



- Sponge-machine for cleaning grout (cement based or epoxy resin) from floors: terracotta, porcelain, double-fired and single-fired tiles, marble, porphyry, natural stone, quarry tile, treaded tile, etc. during the grouting phase.
- Does not pull grout from the joints.
- Performance: 100 sq m/h for medium difficulty surfaces (800 - 1500 s.f. per hour in general).
- Sponge rollers can last from 150 to 2000 sq m (1600 - 21000 s.f.).
- Water is fed to the roller via a foam-reducing rubber belt. So, no pump is needed resulting in no clog up.
- Moisture level of the sponge roller is adjustable via the easy-to-use pressure adjustment lever.
- Separate lever adjusts the front wheels height.
- Easy-to-replace sponge roller thanks to the magnetic "quick clutch" system.
- The handle folds down for transport and storage. Also thanks to its ergonomic design, handle is fully adjustable for height and angle according to the user(s) needs.
- Die cast aluminium body reduces weight while increasing overall strength and durability.
- Easy-to-remove water-tank (15 liters/4 gal) made of impact resistant plastic to prevent breakage.
- Supplied with: sponge roller for cement based grout, anti-foaming liquid, user and maintenance.
- Sponge roller for epoxy-based grouts available as accessory.

MODEL SPECIFICATIONS

Part No.	Barcode	Box	Lightning Bolt	M	Sponge Roller	Water Tank	Roller	Roller
399 ADV	8024648004529	1	230 V 50/60 Hz	Single-phase	0,16 HP / 0,12 kW	2800/3360	"Havana" sponge	21 / 25
399 ADV GB	8024648009685	1	110 V 50 Hz	Single-phase	0,16 HP / 0,12 kW	2800		21
399 ADV USA	8024648009692	1	110 V 60 Hz	Single-phase	0,16 HP / 0,12 kW	3360		25

DIMENSIONS AND WEIGHT

Model	Dimensions (cm)	Dimensions (in)	Weight (Kg)	Weight (lbs)	Dimensions (cm)	Dimensions (in)	Weight (Kg)	Weight (lbs)
BERTA ADV	65x55xh 50 cm	25 3/8" x 21 5/8" x h 20"	29 Kg	64 lbs	73x60xh 55 cm	29" x 23 5/8" x h 21 5/8"	32 Kg	70.5 lbs



ELECTROSPONGES



AVAILABLE SPONGE



SWEEPEX SPONGE ROLLER
CELLULOSE SPONGE ROLLER
HAVANA SPONGE ROLLER

ACCESSORIES



SWEEPEX SPONGE ROLLER
CELLULOSE SPONGE ROLLER
ANTI FOAMING LIQUID

PACKAGE



CARTON BOX ON PALLET
OVERLAPABLE PALLETS

TECHNICAL CHARACTERISTICS



HAVANA SPONGE ROLLER
ADJUSTABLE SQUEEZING
ADJUSTABLE PRESSURE
WATER DRAGGING WITHOUT PUMP
BUMPER FOR SPONGE PROTECTION
FOLDING HANDLE
BUCKET CAPACITY
REDUCER
CHAIN TRANSMISSION

- Electro-sponge for cleaning grout (cement based or epoxy resin) from floors: Terracotta, porcelain, double-fired and single-fired tiles, marble, clinker, porphyry, natural stone, quarry tile, treaded tile, etc. during the grouting phase.
- Does not pull grout from the joints. Suggested for medium and large surfaces
- Performance: 100 sm/h for medium difficulty surfaces (800 - 1500 s.f. per hour in general).
- Sponge rollers can last from 150 to 2000 sm (1600 - 21000 s.f.).
- Variable pressure wringer allows for manual adjustment of the water saturation level of the sponge.

- Sponge roller pressure on the floor is adjustable (for textured or treaded surfaces).
- Water is fed to the roller via a foam reducing belt (no pump to clog up).
- Folding, ergonomic handle with adjustable working angle. This handle also doubles as a storage stand when the machine is not in use.
- Removable tank (16 liters).
- Supplied with: sponge roller for cement based grout, user and maintenance manual.

MODEL SPECIFICATIONS

Part No.								
380DF	8024648003249	1	230 V 50/60 Hz	Single-phase	0,5 HP / 0,37 kW	1400 / 1680	"Havana" sponge	18 / 22

DIMENSIONS AND WEIGHT

Model				
ROSINA	100x50xh 55 cm	40"x20"xh 21 5/8"	56 Kg 123.5 lbs	100x60xh 75 cm 40"x23"xh 29" 67 Kg 147.7 lbs



SPONGE ROLLERS AND ANTIFOAM LIQUID

MADE IN ITALY



380RULLO



AVANA



380RULSWE



SWEEPEX



380RULEPO



CELLULOSA



380ANTISC400



380ANTISC

PACKAGE



CARTON BOX

- Sponge roller "Havana" (brown) for cement based grout.
- Sponge roller "Sweepex" (soft yellow) high absorption for cement based grout.
- Sponge roller "Cellulose" (dense yellow) for epoxy resin based grout.

- Antifoaming liquid for use on heavy latex modified grouts to avoid foaming.
- Dosage 5 ml x liter of water (1/2 oz. - 1 oz. per Gallon)
- Available in 100 gr and 400 gr (3.5 and 14 oz) bottles.

SPONGE ROLLER

Part No.			Sponge	Roller dimension							
380RULLO	8024648004925	4	Havana	Ø 295x400 mm	Ø 11 5/8" x 15 3/4"	1,9 Kg	4.2 lbs	70x55xh 40 cm	27 1/2"x22"xh 15"	9,6 Kg	21.2 lbs
380RULSWE	8024648003263	4	Sweepex			2 Kg	4.4 lbs			10 Kg	22 lbs
380RULEPO	8024648003270	4	Cellulose			2,3 Kg	5 lbs			11,2 Kg	24.7 lbs

ANTIFOAMING

Part No.										
380ANTISC400	8024648011800	5	400 gr	14 oz	470 gr	16.6 oz	20x20xh 15 cm	8"x8"xh 6"	3 Kg	6.6 lbs
380ANTISC	8024648003256	10	100 gr	3.5 oz	120 gr	4.2 oz	27x10xh 15 cm	10 5/8"x4"xh 6"	1,3 Kg	2.9 lbs

ELECTROSPONGES